



Technical Bulletin

Alcho-Re Paste Flux

DESCRIPTION

Alcho-Re Paste Flux is a super-saturated solution of resin flux, suitable for general soldering in electrical and electronic applications, where non-corrosive residues are required.

FEATURES AND BENEFITS

- Mildly activated (RMA type) and particularly effective on clean copper or tinned surfaces. Ideal for machine soldering of copper leads and tags.
- Non-corrosive residues – when heat is applied the paste becomes a viscous liquid. Once soldering is complete and heat is withdrawn, the flux forms a hard, non-corrosive residue (conforms to specification DTD599A).
- Suitable for use with both tin-lead and lead free solders for a wide variety of applications.
- Having a creamy consistency, Alcho-Re Paste flux is particularly suited to assemblies where joint surfaces are not horizontal, as unlike a liquid flux, it remains in place on the joint surfaces before the process begins.

APPLICATION

The flux can be easily applied to the required areas of the work-piece by brushing or any other suitable means. Oven or induction heating is acceptable provided the heating time is not excessive.

AVAILABILITY

450 g containers.

PHYSICAL/CHEMICAL PROPERTIES

Appearance:	Amber Paste
Specific Gravity:	1.0 @20°C
Flash Point:	Closed cup 12°C
Acid Number:	133 mg KOH/g
Odour:	Characteristic alcohol

HEALTH AND SAFETY

Observe standard precautions for handling and use of corrosive liquids. Eye and skin protection must be provided. Avoid breathing fumes evolved during soldering. Adequate fume extraction should always be provided. For detailed information refer to the relevant Health and Safety Data Sheet (MSDS) available on request.

The information contained herein is based on data considered accurate and is offered at no charge. No warranty is expressed or implied regarding the accuracy of this data. Liability is expressly disclaimed for any loss or injury arising out of the use of this information or the use of the materials designated.