



SOLDER CONNECTION

Email: sales@solderconnection.co.uk | Tel: +44(0)1291 624 400

QUALITEK® Technical Bulletin

Water Soluble Rework Wand

DESCRIPTION

Qualitek® Rework Wands are flux-filled applicator pens designed for hand-soldering assembly or rework applications of circuit boards. Water Soluble Rework Wands were designed for complete water solubility of post-soldering residues.

FEATURES AND BENEFITS

- Easy application of flux to specific areas
- Water Soluble flux
- Heat sensitive applicator pen available

TECHNICAL DATA

	Specification
Flux Classification	ORH1
Color and Appearance	Colourless liquid
Copper Mirror	Complete removal
Flash Point	12°C
Solids Content	17.5
Shelf Life	Indefinite

PACKAGING

10ml Flux Pen

CLEANING

For organic based Water Soluble flux pens, we recommend hot deionized water (49 °C) for residue removal.

STORAGE & SHELF LIFE

Recommended storage is at room temperature away from ignition sources. The shelf life for this product is indefinite.

DISPOSAL

Rework Wands contain hazardous ingredients, therefore, should be disposed of in accordance with local, regional and national requirements.

APPLICATION

Apply pressure to the tip of the Rework Wand to apply the desired amount of flux to a specific area. Apply additional flux as needed.

The information contained herein is based on data considered accurate and is offered at no charge. No warranty is expressed or implied regarding the accuracy of this data. Liability is expressly disclaimed for any loss or injury arising out of the use of this information or the use of the materials designated.

Issue 1 - 23/03/23