

# SOLDER CONNECTION

Email: [sales@solderconnection.co.uk](mailto:sales@solderconnection.co.uk) | Tel: +44(0)1291 624 400



## Precision Cleaning Technologies for the Electronics

### Desoldering Braid

**Desoldering braid (wick)** is **pre-fluxed** copper braid that is used to remove solder, which allows components to be replaced and excess solder to be removed.


Techspray No-Clean wick is coated with proprietary flux that only leaves a slight clear residue, which does not cause service issues. Cleaning after using Techspray No-Clean wick is optional.

All Techspray braid works with both lead and lead-free soldering processes.

### Pro-Wick Rosin – ESD-Safe Bobbin

For the fastest wicking action, rosin flux coated braid is ideal for high volume PCB production/repair environments.




	Size/Color	1.5m (5')	3.0m (10')	7.6m (25')	15.2m (50')	30.4m (100')
	<b>1808</b> #1 White (0.9mm)	1808-5F	1808-10F			
	<b>1809</b> #2 Yellow (1.4mm)	1809-5F	1809-10F			
	<b>1810</b> #3 Green (1.9mm)	1810-5F	1810-10F			1810-100F
	<b>1811</b> #4 Blue (2.5mm)	1811-5F	1811-10F	1811-25F		1811-100F
	<b>1812</b> #5 Brown (3.3mm)	1812-5F				

### No-Clean Wick – ESD-Safe Bobbin

The cleanest No-Clean braid in the industry. The proprietary flux formula is specially designed to avoid catastrophic and latent PCB failures caused by ionic flux residue.



	Size/Color	1.5m (5')	3.0m (10')	7.6m (25')	15.2m (50')	30.4m (100')
	<b>1820</b> #1 White (0.9mm)		1820-10F			
	<b>1821</b> #2 Yellow (1.4mm)	1821-5F	1821-10FT	1821-25F	1821-50F	
	<b>1822</b> #3 Green (1.9mm)	1822-5F	1822-10F			1810-100F
	<b>1823</b> #4 Blue (2.5mm)	1823-5F	1823-10F			1823-100F
	<b>1824</b> #5 Brown (3.3mm)	1824-5F		1824-25F		
	<b>1825</b> #6 Red (4.9mm)	1825-5F				

Specifications: Meets IPC Standard 7711 and ANSI J Standard 001C for circuit board repair and rework (Applies to 2505, 2506, 2507, 2509)