

Ultraclean CBX Technical Data Sheet



Description

Ultraclean CBX is strong alkaline detergent for general use in ultrasonic baths:

- Aqueous based product
- Heavy oil and carbon contaminant removal
- Improves surface tension & enhances ultrasonic performance
- Contains de-foaming agent
- Not suitable for use on aluminium

Applications

Ultraclean CBX is used to remove heavy oil and carbon from parts and components in manufacturing and processing industries. (Not suitable for processing aluminium or other soft metals. Instead, please use Ultraclean SA).

Directions for Use

Add 20-50ml of Ultraclean CBX per 1 Litre of water in the ultrasonic cleaner. Do not mix with other solutions. The required dosage will depend on your cleaning application and the level of contamination. Items should be rinsed with water and dried immediately after processing.

Technical Data

These figures are typical and should not be interpreted as specifications, refer to the product safety data sheet for details

Characteristic	Value/Description
Appearance	Light brown liquid
Odour	Characteristic
pH (@ 1%)	13
Relative Density at 20°C	1.05

Supplied as:

- 6 x 1Litre Bottles (SKU: F50004)
- 20 Litre Drum (SKU: F500003)

Disposal

When diluted to concentration of 5% or less, Ultraclean CBX is not hazardous to aquatic organisms and may be safely disposed of down the drain. Refer to regional or national regulations.

Storage

Store in a cool, dry place protected from frost and away from acids and strong oxidising agents. Store upright in original containers. Shelf-life up to 1year from date of manufacture.

Specifications are subject to change for continual improvements