



Solder Pots

100-4C Lead Free Solder Pot:

- Closed-loop sensor controls temperature. Zero triggering without polluting the operating voltage.
- Adopts anti-erosion and heat resistant alloy materials; Long life time; Suitable for lead free applications.

Heating Power	200 Watt
Temperature Range	150-500°C
Pot Size	100mm Dia. x 40mm Deep
Outer Dimensions	100x100x40
Weight	approx. 1.5kg
Pot Material	Titanium Alloy

100-C Lead Free Solder Pot:

- Closed-loop sensor controls temperature. Zero triggering without polluting the operating voltage.
- Adopts anti-erosion and heat resistant alloy materials; Long life time; Suitable for lead free applications.

Heating Power	200 Watt
Temperature Range	150-500
Pot Size	100mm Dia. x 40mm Deep
Outer Dimensions	100 x 100 x 75(H)mm
Weight	approx. 1.5kg
Pot Material	Titanium Alloy

100-15S Solder Pot:

- Closed-loop sensor controls temperature. Zero triggering without polluting the operating voltage.
- Adopts anti-erosion and heat resistant alloy materials; Long life time; Suitable for lead free applications.
- Rapid temperature rising; Temperature accurate and stable.
- LCD displays the temperature.
- Calibrate temperature digitally. Easy and convenient to use.



Heating Power	600 Watt
Temperature Range	150-450°C
Pot Size	91(L) x 135(W) x 60(H)mm
Outer Dimensions	200(L) x 330(W) x 110(H)mm
Weight	approx. 5.5kg
Pot Material	Titanium Alloy